

# Data Connector: Data Dictionary

Last updated: 2023-11-09

## Table of Contents

<b>Common Fields</b>	<b>1</b>
Primary ID	1
Created At	1
Updated At	1
<b>Tables</b>	<b>2</b>
catalog_page	2
catalog_page_student_group_visibility	2
certificate	3
course	4
course_series	4
course_series_published_courses	5
domain	5
domain_access_code	5
domain_access_code_pool	5
domain_membership	6
domain_signup_field	6
domain_signup_info	7
enrollment	7
lesson	8
offer	8
plan	9
plan_enrollment	9
plan_tag	9
promo_code	10
promo_code_pool	10
published_course	11
published_course_student_group_visibility	11
published_course_tag	11
purchase	12
quiz	13
quiz_answer	13
quiz_question	14
quiz_question_bank	14

quiz_question_bank_assignment	15
quiz_question_response	15
quiz_question_response_chosen_answers	16
quiz_response	16
scorm_interaction	17
scorm_resource	17
student	18
student_course_progress	18
student_group	18
student_group_membership	19
student_lesson_progress	19
student_sco_progress	20
tag	20
training_credit_code	21
training_credit_code_offer	21
training_credit_code_student_group	21
vilt_account	22
vilt_calendar_account	22
vilt_session	22
vilt_session_event	23
vilt_session_registration	23
vilt_session_tag	23
web_package	24
path	24
published_path	24
student_path_progress	24
published_path_enrollment	25
path_item	25
student_path_item_progress	26
published_path_tags	26

# Common Fields

There are a few common fields on all tables.

## Primary ID

Each table has a primary ID field. The ID is an alphanumeric (lowercase) field up to 32 characters long. The value of the ID is unique across all instances of the particular table, but not necessarily globally unique across all IDs within Skilljar.

Naming of the primary ID field is typically the table name suffixed with “\_id”.

## Created At

The “created\_at” field is a datetime indicating when the given row was created within Skilljar.

## Updated At

The “updated\_at” field is a datetime indicating when the given row was last updated within Skilljar.

# Tables

## catalog\_page

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
catalog_page_id	char	varying(32)	Unique id of the catalog page
domain_id	char	varying(32)	Unique id of the domain on which the catalog page belongs
is_visible	bool		Whether or not the catalog page is visible or hidden by default
page_title	char	varying(500)	Title of catalog page

## catalog\_page\_student\_group\_visibility

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
catalog_page_student_group_visibility_id	char	varying(32)	Unique id of the catalog_page_student_group_visibility
catalog_page_id	char	varying(32)	Unique id of the catalog_page on which this relationship belongs
is_visible	bool		The visibility relationship of the catalog page with the group: can the group see the catalog page, or is it hidden from the group.
student_group_id	char	varying(32)	Unique id of the student_group on which this relationship belongs

## certificate

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
certificate_id	char	varying(32)	unique id of the certificate

code	char	varying(12)	unique code for the certificate used to create a public url
completed_at	datetime		timestamp when the certificate was completed
expires_at	datetime		timestamp for when the certificate will expire
url	char	varying(255)	public url to access the certificate

## COURSE

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
course_id	char	varying(32)	unique id of the course
title	char	varying(500)	title of the course
issue_certificate_upon_completion	bool		Whether or not to issue certificates upon course completion

## COURSE\_SERIES

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
course_series_id	char	varying(32)	unique id of the course series
domain_id	char	varying(32)	unique id of the domain on which the course series belongs
title	char	varying(500)	title of the course series
visible_on_catalog	bool		whether or not the course series is visible on the catalog page (True/False)

## COURSE\_SERIES\_PUBLISHED\_COURSES

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
course_series_publis	char	varying(32)	unique id of the course_series_published_course

hed_course_id			
course_series_id	char	varying(32)	unique id of the course series
published_course_id	char	varying(100)	unique id of the published course in the series

## domain

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
domain_id	char	varying(32)	unique id of the domain
name	char	varying(225)	domain name

## domain\_access\_code

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
domain_access_code_id	char	varying(32)	unique id of the access code
code	char	varying(255)	value of the access code
use_count	int		how many times the access code has been used
max_uses	int		how many times the access code can be used total
is_active	bool		whether or not the access code is active and can be used (True/False)
domain_access_code_pool_id	char	varying(32)	unique id of the access code pool the access code belongs to

## domain\_access\_code\_pool

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
domain_access_code_pool_id	char	varying(32)	unique id of the access code pool

name	char	varying(255)	the name of the access code pool
domain_id	char	varying(32)	unique id of the domain the access code pool belongs to
channel	char	varying(20)	How the access code pool was created (API, Import, Dashboard, E-Commerce, Unknown)
starts_at	datetime		When codes within this pool become active
expires_at	datetime		When codes within this pool cease to be active

## domain\_membership

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
domain_membership_id	char	varying(32)	unique id of the domain membership
is_active	bool		whether or not the domain membership is active
expires_at	datetime		timestamp when the domain membership will expire
domain_id	char	varying(32)	unique id of the domain
domain_access_code_id	char	varying(32)	unique id of the access code
student_id	char	varying(32)	unique id of the student

## domain\_signup\_field

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
domain_signup_field_id	char	varying(32)	unique id of the signup field
label	char	varying(100)	name of the signup field
domain_id	char	varying(32)	unique id of the domain the signup field belongs to

## domain\_signup\_info

This table represents an individual student's response of a signup field.

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
domain_signup_info_id	char	varying(32)	unique id of the signup info
value	char	varying(100)	the customer value provided for the signup info
domain_membership_id	char	varying(32)	unique id of the domain membership the signup info belongs to
domain_signup_field_id	char	varying(32)	unique id of the signup field the signup info belongs to

## enrollment

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
enrollment_id	char	varying(32)	unique id for the enrollment
enrolled_at	datetime		timestamp of when the student first became enrolled in the course
expires_at	datetime		timestamp of when the course enrollment expires
is_active	bool		whether or not the student has access to the published course from this enrollment
certificate_id	char	varying(32)	unique id of the certificate earned for the course
published_course_id	char	varying(32)	unique id of the published course enrolled in
purchase_id	char	varying(32)	unique id of the purchase this enrollment corresponds to
student_id	char	varying(32)	unique id of the student
student_course_progress_id	char	varying(32)	unique id of the student course progress
channel	char	varying(25)	method in which this enrollment was created

## lesson

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created



updated_at	datetime		timestamp of when the object was last updated
lesson_id	char	varying(32)	unique id of the lesson
is_section	bool		indicates whether the lesson is a section/header
is_optional	bool		when enabled, the lesson will not be required for course completion
type	char	varying(12)	the type of the lesson (e.g. ASSET, HTML, QUIZ, VILT, WEB_PACKAGE, IE_EXAM)
title	char	varying(500)	the title of the lesson
order	int		the order in which this lesson appears within the course
course_id	char	varying(32)	unique id of the course
quiz_id	char	varying(32)	unique id of the quiz (if applicable)
web_package_id	char	varying(32)	unique id of the web package (if applicable)

## offer

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
offer_id	char	varying(32)	unique id of the offer
domain_id	char	varying(32)	unique id of the domain this offer belongs to
published_course_id	char	varying(32)	unique id of the published_course this offer belongs to
course_series_id	char	varying(32)	unique id of the course_series this offer belongs to
published_path_id	char	varying(32)	unique id of the published_path this offer belongs to
offer_type	char	varying(32)	unique id of the published_course this offer belongs to
price_cents	int		listed price in cents
currency_code	char	varying(32)	listed currency code
sku	char	varying(32)	listed sku
max_quantity	int		listed max_quantity
is_active	bool		whether or not the offer is active
price_credits	int		listed price in training credits

## plan

Field name	Format	Length	Description
------------	--------	--------	-------------

created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
plan_id	char	varying(32)	unique id of the plan
domain_id	char	varying(32)	unique id of the domain this plan belongs to
name	char	varying(500)	plan name
slug	char	varying(100)	slug of the plan
is_visible	bool		whether or not this plan is visible by default

## plan\_enrollment

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
plan_enrollment_id	char	varying(32)	unique id of the plan enrollment
plan_id	char	varying(32)	unique id of the plan attached to this plan enrollment
purchase_id	char	varying(32)	unique id of the purchase that was used to create this plan enrollment
expires_at	datetime		timestamp of when the plan enrollment expires
enrolled_at	datetime		timestamp of when the plan enrollment started
is_active	bool		Whether the plan enrollment is currently active

## plan\_tag

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
plan_tag_id	char	varying(32)	unique id of the plan tag
plan_id	char	varying(32)	unique id of the plan associated with this plan tag
tag_id	char	varying(32)	unique id of the tag associated with this plan tag

## promo\_code

Field name	Format	Length	Description
------------	--------	--------	-------------

created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
promo_code_id	char	varying(32)	unique id of the promo code
code	char	varying(40)	value of the promo code
use_count	int		number of times the promo code has been used
max_uses	int		maximum number of times the promo code can be used
is_active	bool		whether or not this promo code is active and can be used
promo_code_pool_id	int	varying(32)	unique id of the promo code pool the promo code belongs to

## promo\_code\_pool

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
promo_code_pool_id	char	varying(32)	unique id of the promo code pool
name	char	varying(255)	name of the promo code pool
bulk_purchase_id	char	varying(32)	unique id of the purchase - this is only present when the code was a result of a bulk purchase
is_active	bool		whether or not this promo code pool is active and can be used
starts_at	datetime		Indicating the start of the promo code pool
ends_at	datetime		Indicating the end of the promo code pool

## published\_course

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
published_course_id	char	varying(32)	unique id of the published course
is_live	bool		whether or not the published course is live
url	char	varying(255)	the url of the published course
course_id	char	varying(32)	unique id of the course being published
domain_id	char	varying(32)	unique id of the domain the course is published on

visible_on_catalog	bool		whether or not the published course is visible on the catalog page (True/False)
is_visible	bool		whether this published course is visible to all users by default (this may be overridden at the student group level by published_course_student_group_visibility)

## published\_course\_student\_group\_visibility

This table represents student group overrides to published course visibility.

Field name	Format	Length	Description
published_course_student_group_visibility_id	char	varying(32)	unique id of the published course student group visibility
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
published_course_id	char	varying(32)	unique id of the published course this is overriding visibility for
student_group_id	char	varying(32)	unique id of the student group this is overriding visibility for
is_visible	bool		whether this override makes the published course visible to the specified student groups (override can either hide courses that are visible by default or make courses that are hidden by default visible)

## published\_course\_tag

Field name	Format	Length	Description
published_course_tag_id	char	varying(32)	unique id of the published course tag
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
published_course_id	char	varying(32)	unique id of the published course this tag is applied to
tag_id	char	varying(32)	unique id of the tag being applied

## purchase

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
purchased_at	datetime		timestamp of when the actual purchase occurred
purchase_id	char	varying(32)	unique id of the purchase
refunded_at	datetime		timestamp of when the purchase was refunded
order_id	char	varying(20)	unique id for use in order reports
state	char	varying(10)	status of the purchase (SUCCESS, FAILED, REFUNDED, etc.)
payment_processor	char	varying(10)	name of the payment processor used (Stripe, PayPal, etc.)
payment_processor_account_id	char	varying(512)	unique id of the account in the payment processor's system (Stripe Charge ID, PayPal Payment ID, etc.)
payment_processor_order_id	char	varying(128)	unique id of the payment in the payment processor's system
price_cents	int		listed price in cents
price_currency	char	varying(3)	listed currency
quantity	int		quantity purchased
promo_code_id	char	varying(32)	unique id of the promo code if one was used
promo_code_price_cents	int		listed price in cents (promo code)
promo_code_quantity	int		quantity of promo codes used
student_id	char	varying(32)	unique id of the student this purchase belongs to
offer_id	char	varying(32)	unique id of the offer that was purchased
offer_sku	char	varying(32)	listed sku (copied from offer at time of purchase)
offer_price_cents	int		listed price in cents (copied from offer at time of purchase)
price_credits	int		payment amount in training credits
training_credit_code_id	char	varying(32)	unique id of the training credit code that was use for purchase
bulk_promo_code_generated_id	char	varying(32)	unique id of the promo code generated during

			a bulk purchase
--	--	--	-----------------

## quiz

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_id	char	varying(32)	unique id of the quiz
name	char	varying(100)	name of the quiz
passing_percentage_correct	int		the minimum percentage of questions correct needed to pass the quiz
max_attempts	int		the maximum number of quiz attempts permitted
require_correct_response	bool		whether or not incorrect answers to questions are accepted
randomize_questions	bool		whether or not questions are assigned in a random order
limit_question_count	int		limits the number of questions assigned per quiz attempt (only respected if randomize_questions is set)
randomize_answers	bool		whether or not answers are shown in a random order (applies to every question)
time_limit_seconds	int		The time limit of a quiz in seconds. Blank means the students have unlimited time to complete the quiz

## quiz\_answer

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_answer_id	char	varying(32)	unique id of the answer
order	int		the order in which this answer appears within the question
is_correct	bool		whether or not the answer is considered correct for the question
text	char	varying(1000)	the value of the answer
quiz_question_id	char	varying(32)	unique id of the quiz this answer belongs to

## quiz\_question

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_question_id	char	varying(32)	unique id of the quiz question
type	char	varying(20)	the question type ('MULTIPE_CHOICE', 'MULTIPLE_ANSWER', 'FILL_IN_THE_BLANK', 'FREEFORM')
order	int		the order in which this question appears within the quiz (only respected if randomize_questions is not set on the quiz)
html	text		the HTML formatted value of the question
quiz_id	char	varying(32)	unique id of the quiz this question belongs to
quiz_question_bank_id	char	varying(32)	Unique id of the question bank this question belongs to
requires_manual_grading	bool		whether or not this question needs to be manually graded after submitting a response - a quiz with any question in this state will trigger the manual quiz grading workflow

## quiz\_question\_bank

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_question_bank_id	char	varying(32)	unique id of the quiz question bank
name	char	varying(100)	Name of the question bank

## quiz\_question\_bank\_assignment

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created

updated_at	datetime		timestamp of when the object was last updated
quiz_question_bank_assignment_id	char	varying(32)	unique id of the quiz question bank
quiz_question_bank_id	char	varying(32)	unique id of the question bank
quiz_id	char	varying(32)	Unique id of the quiz the question bank is assigned to
order	int		Order of the question bank in the quiz
randomize_questions	bool		Should the questions of the question bank be shown in a random order
limit_question_count	int		Limit the number of questions that will be asked from the question bank

## quiz\_question\_response

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_question_response_id	char	varying(32)	unique id for the quiz question response
order	int		the order in which the question appeared for the quiz attempt
is_correct	bool		nullable value by default, returns whether or not the response was considered correct for the question (True/False),
submit_count	int		number of times the question was attempted within a single quiz attempt
started_at	datetime		timestamp of when the question response was started
finished_at	datetime		timestamp of when the question response was finished
grader_feedback	char	varying(5000)	feedback provided by the grader (only provided in the case of manual grading)
quiz_answer_id	char	varying(32)	unique id for the student's answer (does not apply for Multiple Answer questions)
quiz_response_id	char	varying(32)	unique id for the quiz response this belongs to
quiz_question_id	char	varying(32)	unique id for the question this is in response to
response_text	char	varying(5000)	the student's provided free-form answer (only applies for Fill in the Blank & Free Form)



			questions)
randomize_answers	bool		whether or not the answer choices were shown in a random order

## quiz\_question\_response\_chosen\_answers

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_question_response_chosen_answer_id	char	varying(32)	unique id of the quiz question response chosen answer
quiz_answer_id	char	varying(32)	unique id of the chosen answer
quiz_question_response_id	char	varying(32)	unique id of the question response this belongs to

## quiz\_response

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
quiz_response_id	char	varying(32)	unique id of the quiz response
completed_at	datetime		timestamp of when the response was considered complete and results became available
graded_at	datetime		timestamp of when the response was manually graded via the dashboard (only applies when a question has requires_manual_grading set)
correct_response_count	char	varying(12)	number of questions the student answered correctly
is_passed	bool		whether or not the student passed the quiz (True/False)
started_at	datetime		timestamp of when the student started taking the quiz
finished_at	datetime		timestamp of when the student finished taking the quiz
question_count	int		total number of questions in the quiz
quiz_id	char	varying(32)	unique id of the quiz
student_lesson_progress_id	char	varying(32)	unique id of the student lesson progress this

			belongs to
attempted_question_count	int		The number of questions the student answered (correctly or incorrectly)

## scorm\_interaction

Field name	Format	Length	Description
scorm_interaction_id	char	varying(32)	unique id of the SCORM interaction
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
student_sco_progress_id	char	varying(15)	unique id of the student SCORM progress
identifier	char	varying(255)	unique identifier for the SCORM interaction within its package
type	char	varying(15)	type of the SCORM interaction ('true-false', 'choice', 'fill-in', 'matching', 'performance', 'sequencing', 'likert', 'numeric', 'other')
weighting	char	varying(200)	a factor which is used to identify the relative importance of one interaction compared to another
order	int		the order of the SCORM interaction
time	char	varying(20)	a chronological point in a 24-hour clock which identifies when the interaction was completed
response	char	varying(16000)	the actual student response to the SCORM interaction
result	char	varying(15)	how the system judges the described response

## scorm\_resource

Field name	Format	Length	Description
scorm_resource_id	char	varying(32)	unique id of the the SCORM resource
created_at	datetime		timestamp of when the object was created
web_package_id	char	varying(32)	unique id of the SCORM web package
identifier	char	varying(2000)	unique identifier for the SCORM resource within its package
type	char	varying(32)	content type ('sco', 'asset')

## student

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
student_id	char	varying(32)	unique id of the student
first_name	char	varying(30)	first name of the student
last_name	char	varying(30)	last name of the student
email	char	varying(254)	email address of the student

## student\_course\_progress

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
student_course_progress_id	char	varying(32)	unique id of student course progress
latest_activity_at	datetime		timestamp of the student's most recent activity within the course
completed_at	datetime		timestamp of when the student completed the course
score	int		score the student received on the course (in cases where course is tied to a quiz score)
score_max	int		maximum possible score possible for the course
credits_earned	char	varying(20)	credits earned by the student from taking the course
success_status	char	varying(10)	student's course success status (Passed, Failed)

## student\_group

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
student_group_id	char	varying(32)	unique id of the student group
name	char	varying(100)	name of the student group

## student\_group\_membership

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
student_group_membership_id	char	varying(32)	unique id of the student group membership
student_id	char	varying(32)	unique id of the student
student_group_id	char	varying(32)	unique id of the student group this belongs to

## student\_lesson\_progress

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
student_lesson_progress_id	char	varying(32)	unique id of the student lesson progress
view_count	int		number of times student viewed the lesson
score_max	int		maximum possible score achievable for the lesson (if applicable)
success_status	char	varying(32)	student's lesson success status (Passed, Failed)
lesson_id	char	varying(32)	unique id of the lesson this belongs to
last_viewed_at	datetime		timestamp of when the student last viewed the lesson
student_course_progress_id	char	varying(32)	unique id of the student course progress this belongs to
completed_at	datetime		timestamp of when the student completed the lesson
score	int		score student achieved for the lesson (if applicable)

## student\_sco\_progress

Field name	Format	Length	Description
student_sco_progress_id	char	varying(32)	unique id of the SCORM progress
created_at	datetime		timestamp of when the object was created

updated_at	datetime		timestamp of when the object was last updated
attempted_at	datetime		timestamp of when a new SCORM progress was created. It is used to surface user SCO attempts if a SCO lesson is configured to record multiple attempts.
student_lesson_progress_id	char	varying(32)	unique id for the student lesson progress this belongs to
scorm_resource_id	char	varying(32)	unique id for the SCORM resource this belongs to
score_raw	char	varying(200)	the most recent score the student achieved for the SCORM module
score_min	char	varying(200)	the minimum score for the SCORM module
score_max	char	varying(200)	the maximum score for the SCORM module
total_time	int		total time spent on the SCORM module
status	char	varying(32)	status as reported by the SCORM module ('passed', 'completed', 'failed', 'incomplete', 'browsed', 'not attempted')

## tag

Field name	Format	Length	Description
tag_id	char	varying(32)	unique id of the tag
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
name	char	varying(100)	name of the tag
slug	char	varying(100)	slug of the tag

## training\_credit\_code

Field name	Format	Length	Description
training_credit_code_id	char	varying(32)	unique id of the training credit code
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
code	char	varying(40)	code value of training credit code
available_to_all_students	bool		true if this training credit code can be applied by all students

available_to_all_offers	bool		true if this training credit code can be applied by all offers
credits_used	int	max(2147483647)	total amount of credits used
credits_total	int	max(2147483647)	total amount that training credit code can spend (balance would be credits_total - credits_used)
expiration_date	datetime		timestamp of when this code expires
expire_content	bool		When set to true, content objects purchased with this training credit code will limit student's access to it (including bulk purchase)
tracking_identifier	char	varying(256)	field for external tracking id

### training\_credit\_code\_offer

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
training_credit_code_offer_id	char	varying(32)	unique id of the training_credit_code_offer
credit_code_id	char	varying(32)	unique id of the training credit code
offer_id	char	varying(32)	unique id of the offer

### training\_credit\_code\_student\_group

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
training_credit_code_student_group_id	char	varying(32)	unique id of the training_credit_code_student_group
credit_code_id	char	varying(32)	unique id of the training credit code
student_group_id	char	varying(32)	unique id of the student_group

## vilt\_account

Field name	Format	Length	Description
vilt_account_id	char	varying(32)	unique id of the account
vilt_account_type	char	varying(40)	type of VILT session this account is used for

## vilt\_calendar\_account

Field name	Format	Length	Description
vilt_calendar_account_id	char	varying(32)	unique id of the calendar account
instructor_name	char	varying(100)	name of the instructor
email	char	varying(100)	email of the instructor
active	bool		whether or not this account is active
vilt_account_id	char	varying(32)	unique id of the vilt account this calendar account belongs to

## vilt\_session

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
vilt_session_id	char	varying(32)	unique id of the VILT session
display_name	char	varying(100)	display name of the VILT session
instructor_name	char	varying(100)	name of the instructor affiliated with the VILT session
lesson_id	char	varying(32)	unique id of the lesson this VILT session belongs to
seats_total	int		total number of seats available for the VILT session
instructor_external_id	char	varying(100)	id of the instructor for this session from external authentication
vilt_account_id	char	varying(32)	unique id of the vilt_account for this session
cancelled_at	datetime		timestamp of when the object was cancelled

## vilt\_session\_event

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
vilt_session_event_id	char	varying(32)	unique id of the VILT session event
starts_at	datetime		timestamp of when the event starts / started
ends_at	datetime		timestamp of when the event ends / ended
location	char	varying(100)	location of the event
timezone	char	varying(63)	timezone for when the event starts / ends
vilt_session_id	char	varying(32)	unique id for the VILT session this event belongs to

## vilt\_session\_registration

Field name	Format	Length	Description
vilt_session_registration_id	char	varying(32)	unique id of the VILT registration
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
vilt_session_id	char	varying(32)	unique id of the VILT session this belongs to
student_lesson_progress_id	char	varying(32)	unique id of the student lesson progress this belongs to
attended	bool		whether or not the student attended the VILT session (True/False)

## vilt\_session\_tag

Field name	Format	Length	Description
vilt_session_tag_id	char	varying(32)	unique id of the VILT session tag
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
vilt_session_id	char	varying(32)	unique id of the VILT session this tag is applied to
tag_id	char	varying(32)	unique id of the tag being applied



## web\_package

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
web_package_id	char	varying(32)	unique id of the web package
title	char	varying(500)	title of the web package
type	char	varying(10)	identifies the type of web package (HTML/SCORM)

## path

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
path_id	char	varying(32)	unique id of the path
title	char	varying(500)	title of the path

## published\_path

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
published_path_id	char	varying(32)	unique id of the published_path
domain_id	char	varying(32)	unique id of the domain
path_id	char	varying(32)	unique id of the path
is_visible	bool		Whether or not the catalog page is visible or hidden by default

## student\_path\_progress

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated

student_path_progress_id	char	varying(32)	unique id of the student_path_progress
student_id	char	varying(32)	unique id of the student
path_id	char	varying(32)	unique id of the path
completed_at	datetime		timestamp when the path was completed

## published\_path\_enrollment

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
published_path_enrollment_id	char	varying(32)	unique id of the published_path_enrollment
student_id	char	varying(32)	unique id of the student
published_path_id	char	varying(32)	unique id of the published_path
student_path_progress_id	char	varying(32)	unique id of the student_path_progress
purchase_id	char	varying(32)	unique id of the purchase
expires_at	char	varying(32)	timestamp of when the enrollment will expire
enrolled_at	char	varying(32)	timestamp of when the student enrolled in the path
is_active	bool	varying(32)	Whether or not the enrollment is active

## path\_item

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
path_item_id	char	varying(32)	unique id of the path_item
path_id	char	varying(32)	unique id of the path
course_id	char	varying(32)	unique id of the course
order	int		The order in which this path_item appears

## student\_path\_item\_progress

Field name	Format	Length	Description
------------	--------	--------	-------------

created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
student_path_item_progress_id	char	varying(32)	unique id of the student_path_item_progress
student_path_progress_id	char	varying(32)	unique id of the student_path_progress
student_course_progress_id	char	varying(32)	unique id of the student_course_progress
path_item_id	char	varying(32)	unique id of the path_item

## published\_path\_tags

Field name	Format	Length	Description
created_at	datetime		timestamp of when the object was created
updated_at	datetime		timestamp of when the object was last updated
published_path_tag_id	char	varying(32)	unique id of the published_path_tag_id
published_path_id	char	varying(32)	unique id of the published path this tag is applied to
tag_id	char	varying(32)	unique id of the tag being applied

